

IH105 / IH144 Extended U Bolt

(P 04 40)

for steel, copper and insulated pipes 22 - 172 mm



Features and benefits

- Type IH105: zinc plated, for steel pipe
- other finishes available on request
- Type IH144: nylon coated, for copper pipe

Part No.	D (mm)	D (")	DN	Type	G	H (mm)	Lm1 (mm)	k (mm)	Pack 1
B712 3 035	34	1	25	IH105	M6	117	85	40	100
B712 3 042	42	1 1/4	32	IH105	M10	132	90	55	100
B712 3 049	48	1 1/2	40	IH105	M10	137	90	61	50
B712 3 061	60	2	50	IH105	M10	150	90	70	50
B712 3 076	77	2 1/2	65	IH105	M10	164	90	86	50
B712 3 089	92	3	80	IH105	M12	180	90	102	50
B712 3 115	116	4	100	IH105	M12	205	90	126	25
B712 3 140	142	5	125	IH105	M12	225	90	152	25
B712 3 168	172	6	150	IH105	M12	252	90	182	25
B712 6 022	22	-	-	IH144	M6	106	85	27	1
B712 6 028	28	-	-	IH144	M6	106	85	33	1
B712 6 035	35	-	-	IH144	M6	116	85	40	1

PP-strip is used to isolate copper pipe from any supporting steel structure. Please refer to page Q 05 85. Please specify if required.

