

Evolution Fasteners (UK) Ltd Units 2A & 2B Clyde Gateway Trade Park Dalmarnock Road, Rutherglen, Glasgow G73 1AN Tel: +44 (0)141 647 7100 / Fax: +44 (0)141 647 5100

Email: technical@evolutionfasteners.co.uk



www.evolutionfasteners.co.uk



PRODUCT DATASHEET WAFER HEAD SELF-DRILL DRYWALL SCREW



Product Details

Designed for: The assembly of drywall track and ceiling track systems

Head style: Wafer head
Drive bit: Phillips 2
Thread form: Single

Coating: Electroplated zinc
Shank material: Carbon steel
Material grade: AISI C1022

Fire tested: Yes, to EN-1364-1



Wafer Head Self-Drill Drywall Range

Product Code	Size	Drill Point	Drilling Capacity	Effective Thread Length	Fixture Thickness
WHDZ13	4.2 x 13.0mm	Sharp	0.5 – 1.0mm	8.0mm	10.0mm
WHSDZ12	4.2 x 12.0mm	Tek 2	0.8 – 2.5mm	8.0mm	10.0mm
WHSDZ19	4.2 x 19.0mm	Tek 2	0.8 – 2.5mm	10.0mm	15.0mm
WHSDZ25	4.2 x 25.0mm	Tek 2	0.8 – 2.5mm	18.0mm	25.0mm
WHSDZ50	4.2 x 50.0mm	Tek 2	0.8 – 2.5mm	45.0mm	35.0mm

Technical Data

Hardness Rating (Vickers scale)				
Diameter	Surface Hardness	Core Hardness		
4.2mm	600.0HV	450.0HV		

Ultimate mechanical performance			
Diameter	Tensile Strength	Shear Strength	
4.2mm	9.5kN	6.1kN	

Ultimate pull out values				
Diameter	Drill Point	Steel Thickness		
		1.2mm	1.8mm	2.5mm
4.2mm	Tek 2	1.6kN	2.2kN	4.2kN

NOTE: The results expressed in the datasheet are taken as mean loads from a range of empirical tests and are ultimate unfactored loads. Each specifier or end user should make his/ her own decision on what safety factors to use relevant to their design application (such as BS 5950, EN 1991, etc).

Errors and Omissions Excepted.

ABOUT OUR TESTING



All test results were derived from empirical testing performed by ETAS (Evolution Testing & Analytical Services), a UKAS (United Kingdom Accreditation Service) accredited testing laboratory (Accreditation No. 7485). The following tests were performed to the following standards.

Testing Procedures



7485

Test/ Parameter	Standard/ Method/ Procedure	
Ultimate Tensile	ISO 6892-1: 2009 "Metallic materials – tensile testing – Part 1: Method of test at room temperature".	
Ultimate Shear	MIL-STD-1312-13 "Military Standard: Fastener test method (Method 13) Double shear test".	
Pull Out (Withdrawal Force)	EN 14566: 2009 "Mechanical fasteners for gypsum plasterboard systems. Definitions, requirements and test methods".	
Pull Over	EN 14592: 2008 "Timber structures. Dowel type fasteners. Requirements".	
Hardness	ISO 650 7-1: 2005 "Metallic materials – Vickers hardness test – Part 1: Test method".	
Corrosion Resistance	EN ISO 9227: 2012 "Corrosion tests in artificial atmospheres. Salt spray tests".	
Drilling Time Test	EN 14566: 2009 "Mechanical fasteners for gypsum plasterboard systems. Definitions, requirements and test methods".	

Laboratory Contact Details

Evolution Testing & Analytical Services

Units 2A & 2B Clyde Gateway Trade Park

Dalmarnock Road Rutherglen

South Lanarkshire

G73 1AN

T: (0141) 643 4125 F: (0141) 647 5100 E: sales@etasuk.com