



R-SERIES

LS0H Polypropylene Corrugated Conduit

R-SERIES corrugated conduit is a very economical solution for a variety of applications due to its high flexibility, compression strength and colour range.

Suitable for embedding into floors and walls, R-SERIES is often used for cable assemblies, underfloor wiring and cable tidying.



Features:

- Made from Polypropylene
- Temperature range from -40°C to +120°C
- Black in all sizes, colours available in 20, 25 and 32mm only
- LS0H (Low Smoke Zero Halogen) - * starred items only
- UV resistant (Black only) - * starred items only
- IP40 (when used with RF hinged fittings)

Product Code	Trade Size	Internal Diameter	External Diameter	Coil Size
R07B	7mm	6.9mm	9.9mm	50m
R10B	10mm	8.5mm	11.6mm	50m
R12B	12mm	10.1mm	12.7mm	50m
R16B	16mm	10.7mm	16.0mm	100m
R20B*	20mm	16.8mm	20.0mm	50/100m
R25B*	25mm	19.9mm	25.0mm	50/100m
R32B*	32mm	26.5mm	32.0mm	50m
R40B	40mm	32.4mm	40.0mm	25m
R50B	50mm	41.2mm	50.0mm	25m
R63B	63mm	56.3mm	67.2mm	20m
R75B	75mm	66.5mm	80.0mm	20m

Codes used above are based on Black colour, for other colours replace 'B' with the following: White-(W), Grey-(G), Orange-(OR), Green-(GN), Yellow-(Y) e.g.: R20G.
For colours not listed please ring to ensure you have the correct product code.

* Please note colours are only available for 20mm, 25mm & 32mm.