

Flexi Frames




The BASE & EXTENDER frames are designed to provide stability and spread loads evenly across flat roof surfaces. The galvanised steel frame raises equipment up to 405mm above the flat roof level, permitting quick and easy access for roof maintenance.

Features


- Quick and easy height adjustments
- Fast and easy to install
- Time and cost saving
- Allows maintenance access under the equipment
- No penetration of water proof membrane
- Suitable for multiple ASHP installation on flat roofs

Step One: Assemble a BASE FRAME




ORDER - PH-BF-B

Step Two: Need a bigger frame? Add an EXTENDER FRAME



ORDER - PH-EF-B

Step Three: Connect the BASE & EXTENDER FRAMES together



ORDER - PH-BF-B & PH-EF-B

Related Products

Flexi H Frames
Flexi Foot with Strut
Flexi Foot Universal

The Package

- 4 x Feet • 2 x Box Section
- 2 x Strut Beam with Clamps
- 3 x Adjustable Leg Assembly
- 8 x Pre-Assembled Bolts •

Part Code	Description	Length	Width	Min Height	Max Height	Safe Working Load*	Weight
PH-BF-B	Flexi Base Frame	1200mm	1200mm	300mm	405mm	500kg	30kg
PH-EF-B	Flexi Extender Frame	1200mm	1200mm	300mm	405mm	500kg	24kg

Material	
Feet	Square - 320mm and 500mm square UV stabilised - 90% polypropylene and 10% grp
Legs	50mm diameter, 3mm galvanized steel tube. M24 galvanized steel height adjuster. 3mm galvanized steel U-clevis
Box Beams	38 x 38 x 2.5mm galvanized steel square tube
Cross Beams	41 x 41 x 2.5mm galvanized steel slotted channel
Fixing Bolts	M12 zinc-plated steel

Operating Temperatures: -25°C to + 80°C

The Pump House sales team are available to answer your questions or queries on this product. Our experts are waiting for your call **+44 (0)115 900 5858** or if you prefer send an email to **sales@pumph.co.uk** or visit **www.pumph.co.uk**

