


Product Type Drywall screws
Identification sharp point /Self drill drywall / 60782 3.5 / 4.2 , loose and collated
Intended use Mechanical fasteners for gypsum plasterboard systems
Manufacturer/Importer Aptus Fastener Systems Ltd
 Manufacturing Plant ref: 00250
 Salterwood Drive
 Denby Hall Business Park
 Denby
 Derbyshire
 DE5 8JY

Tested to : EN14566:2008+A1:2009 under system 4
 Test values not specific to fastener length
 Manufacturing plant 00250 with FPC

Essential Characteristics	Ref	Performance	UOM	Technical Specification	Certificate Number
Geometry	L	Pass +/- 1.5mm	mm	EN14566:2008+A1:2009	FPC
Withdrawal Force		Pass 450N min	N	EN14566:2008+A1:2009	FPC
Bending behaviour		Pass 10°		EN14566:2008+A1:2009	FPC
Drilling Performance		Pass <= 1 sec	sec	EN14566:2008+A1:2009	FPC
Coating , zinc plated option		Pass >= 5µ	micron	EN14566:2008+A1:2009	FPC
Coating , phosphate option		48hrs no visible rust		EN14566:2008+A1:2009	FPC
Case Hardness at 0.05mm		Pass 55hrc	HRC	EN14566:2008+A1:2009	FPC
Material		C1018		Carbon steel to EN10016	FPC
Class of corrosion resistance		Pass		48hrs no visible rust	
Reaction to fire		A1			



Stewart Taylor - Director
 On behalf of Aptus Fastener Systems Ltd