



FM PRODUCTS CLIP LINK PIPE CLIPS AND SPACER

Material: Made from heat resistant polypropylene, which withstands the temperature changes in central heating systems and is effective with pipes with temperatures up to 100 degrees Celsius. Most pipes in domestic central heating systems operate at around 70 degrees Celsius

Main Advantages & Benefits:

- Large base design prevents clip being pulled into plaster and gives more support against side loads
- Can be linked together to create large runs.
- Pipe clips have a hinged cover which snaps in to place over the top of the pipe. This ensures an “all round” permanent fixing for the pipe. The pipe can be easily removed for maintenance by opening the clip with the end of a screwdriver
- The double clips within the range offer the same high quality of fixing as the single version but have the following advantages for a double pipe run:
 1. Pipe clips can be attached to the pipe to establish positioning and then fixed
 2. Pipes are always parallel and are more aesthetically pleasing
 3. Saves cost as only one screw, one plug and one drilled hole are required to secure two pipes

The spacer is used to raise the clip to allow the fitting of lagging

Fixing Method: In general, central heating system pipes are classed as a “light” fixing. 5.5mm red plugs and a No.8 gauge screw are normally sufficient to secure the clips in this situation. Ensure the screw is long enough to pass through the pipe clip and fully expand the full length of the fixing plug

Clip Range Availability

Pipe Clip Size	Single Clip Link Clip	Double Clip Link Clip
15mm	YES	YES
22mm	YES	YES
28mm	YES	YES

All specifications are illustrative only and do not constitute recommendations by the manufacturers. Users must satisfy themselves as to the correct product and specification required. The manufacturers do not accept any liability for any loss or damage howsoever caused.