

A2 STAINLESS BLIND RIVET NUTS



Type CSK-A2 - Countersunk Head Knurled Body

Thread Size	Grip Range	Gripmor Part No	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall Length
M3	1.5-3.5	CSK3-A2	5.0	4.9	7.5	1.5	11.5
M4	1.5-4.0	CSK4-A2	6.0	5.9	8.5	1.5	12.5
M5	1.5-4.5	CSK5-A2	7.0	6.9	9.5	1.5	13.5
M5	4.0-6.5	CSK5-6.5-A2	7.0	6.9	9.5	1.5	16.0
M6	1.5-4.5	CSK6-A2	9.0	8.9	11.5	1.5	16.0
M6	4.0-6.5	CSK6-6.5-A2	9.0	8.9	11.5	1.5	18.0
M8	1.5-4.5	CSK8-A2	11.0	10.9	13.5	1.5	18.0
M8	4.0-6.5	CSK8-6.5-A2	11.0	10.9	13.5	1.5	21.0
M10	2.0-4.5	CSK10-A2	13.0	12.9	15.5	1.8	21.0
M10	4.5-7.5	CSK10-7.5-A2	13.0	12.9	15.5	1.8	24.0
M12	2.0-4.5	CSK12-A2	16.0	15.9	19.0	2.0	24.5
M12	4.5-7.5	CSK12-7.5-A2	16.0	15.9	19.0	2.0	27.5

● STAINLESS STEEL A2



Type CS-A2 - Countersunk Head Plain Body

Thread Size	Grip Range	Gripmor Part No	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall Length
M4	1.5-4.0	CS4-A2	6.0	5.9	8.5	1.5	12.0
M5	1.5-4.5	CS5-A2	7.0	6.9	9.5	1.5	13.5
M6	1.5-4.5	CS6-A2	9.0	8.9	11.5	1.5	16.0
M8	1.5-4.5	CS8-A2	11.0	10.9	13.5	1.5	18.0

NOTE: Please consider using knurled type 'CSK-A2' as alternative.

The countersunk head style provides a strong head form and will install flush in a countersunk hole. Suitable for use in material of 1.5mm or greater thickness.

● STAINLESS STEEL A2



Type CS-A2-CE - Countersunk Head Plain Body - Closed End

Thread Size	Grip Range	Gripmor Part No	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall Length
M4	1.3-3.0	CS4-A2-CE	6.1	6.0	7.8	1.0	16.1
M4	2.0-3.7	CS4-3.7-A2-CE	6.1	6.0	7.8	1.0	16.8
M5	1.5-3.5	CS5-A2-CE	7.1	7.0	8.8	1.0	18.5
M5	2.5-4.5	CS5-4.5-A2-CE	7.1	7.0	8.8	1.0	19.5
M6	1.5-3.5	CS6-A2-CE	9.1	9.0	10.8	1.0	21.9
M6	2.5-4.5	CS6-4.5-A2-CE	9.1	9.0	10.8	1.0	22.9
M6	3.5-5.5	CS6-5.5-A2-CE	9.1	9.0	10.8	1.0	23.9
M8	1.8-4.2	CS8-A2-CE	11.1	11.0	13.8	1.5	26.0
M8	2.5-5.0	CS8-5.4-A2-CE	11.1	11.0	13.8	1.5	26.8
M8	4.0-6.6	CS8-6.6-A2-CE	11.1	11.0	13.8	1.5	28.2
M10	2.0-5.5	CS10-A2-CE	13.1	13.0	15.8	1.5	33.4
M10	4.0-7.0	CS10-7.0-A2-CE	13.1	13.0	15.8	1.5	34.9

● STAINLESS STEEL A2

