JCP CONSTRUCTION PRODUCTS



Wire Hanger

Data Sheet

Wirehanger

An all steel, hammer in fixings offering increased fire resistance. Suitable for use in concrete, masonry and some natural stone. Zinc plated and yello passivated min 5µm

Hammer In Fixing

Pull down expansion



Through Fixing

Anchor Diameter	mm	6.0
Anchor Length	mm	55.0
Eye Diam.	mm	6.0
Drill Hole Diam	mm	6.0
Min. Hole Depth	mm	40.0
Rec. Tensile Loads	kΝ	1.5

Loads are for 30 N/mm² Concrete

Wire Hangers are suitable for use in solid concrete, hard concrete blocks, hard natural stone and some solid bricks.

Typical Applications:

Suspended Ceiling Hangers, Suspended cables, Bird wires.

Installation Instructions



- 1. Drill correct diameter hole to correct depth in base material.
- 2. Clean hole by brushing and blowing

Milton Keynes

3. Hammer in Wirehanger and pull firmly down

SALES OFFICES

Stone 01785 819819 Dartford 01322 277733 01793 527829 Swindon Elland 01422 370121 01908 330050



JCP Construction Products, Unit 14 Teddington Business Park, Station Rd, Teddington, Middlesex TW11 9BQ Tel 020 8943 1800 Fax 020 8943 1140 Website www.jcpfixings.co.uk