

Description

Component for joining sections of trays using the Click system. It is suitable for all widths of Rejiband trays of heights 35, 60 and 100 mm, with surface protection. It is assembled without the need for any special tools and allows the joining between sections of Rejiband trays in less time, ensuring the mechanical strength of the joint and electrical continuity, according to IEC61537 standard. Made of steel and available in various finishes.

Advantages

It is installed on the tray without screws.

Simple and quick assembly without the need of special tools.

Electrical continuity guaranteed according to standard IEC61537.

Available in various finishes: electro-zinc, bichromate, hot dip galvanised or organic mineral, depending on the type of application.

Applications

Suitable for the fast connection of Rejiband trays in electrical and/or telecommunications installations in: Civil works, Tunnels, Car Parks, Public Buildings, Shopping Centres, Large Infrastructures, Airports, Metro Lines, Railway. Tertiary Sector and industrial applications: Naval, Petrochemical, Textile, Chemical, Food.

Solutions








www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Main technical characteristics

 E.G., Bycro (BC), H.D.G., C8	 25 u	 Steel with surface coating	 -50°/ 150°	 A1 No combustible	ETIM EC002413
--	--	--	--	---	------------------

Product data

	Class  61537	Ref	kg/u
E.G.	Class 3	64010020	0,075
Bycro (BC)	Class 5	64020030	0,075
H.D.G.	Class 5	64030030	0,077
C8	Class 8	64080030	0,075

Coatings

- EZ** - Electrogalvanized, white, according to EN ISO 2081. Class 3 protection in compliance with product standard EN 61537. Electrolytic zinc protection adequate for indoor installations.
- BC** - Electrogalvanized Bycro, yellow, in compliance with EN ISO 2081. Class 4 protection in compliance with product standard EN 61537. Improved resistance to corrosion, especially adequate for demanding indoor installations.
- GC** - Hot-dipped galvanizing in compliance with EN ISO 1461. Class 6 protection in compliance with product standard EN 61537. Appropriate for outdoor installations and aggressive environments.
- BLACK C8** - High Resistance coating, Black Colour. Class 8 of protection in compliance with product standard EN 61537. Neutral Salt Spray Chamber test >1000 h acc. to ISO 9227.
- 304 and 316L** stainless steel, in compliance with EN 10088 standard, with passivated Thermicon treatment. Class 9 protection. Appropriate for outdoor installations and highly aggressive environments.

Product applications

