



C-SERIES

PVC Covered Steel Conduit

Designed to provide high mechanical protection in a highly flexible format C-SERIES can be used in a wide range of dynamic and static applications as well as commercial and industrial environments.

A unique vacuum extrusion process allows C-SERIES to have a thin PVC jacket, which does not restrict the excellent flexibility characteristics of the inner core and also offers a degree of weather proofing.



Features:

- Plain galvanised steel core with PVC (polyvinyl chloride) covering
- Temperature range: -20°C to +70°C
- Ingress Protection: IP54 with CF fittings
- Light weight style with excellent flexibility
- Flame retardant and oil/sunlight resistant to UL360
- LFH, IEMI, RoHS compliant
- Conforms to BSI BS EN 61386

Product Code	Trade Size	Internal Diameter	External Diameter	Minimum Bend Radius	Coil Size
C10	10mm	7.0mm	10.0mm	35.0mm	50m
C12	12mm	10.0mm	14.0mm	40.0mm	50m
C16	16mm	13.0mm	17.0mm	50.0mm	50m
C20	20mm	17.0mm	21.5mm	65.0mm	50m
C25	25mm	21.0mm	26.0mm	75.0mm	50m
C32	32mm	28.5mm	34.0mm	100.0mm	50m
C40	40mm	37.5mm	43.5mm	125.0mm	30m
C50	50mm	48.5mm	56.0mm	175.0mm	20m
C75	75mm	78.0mm	87.5mm	225.0mm	10m
C100	100mm	102.0mm	112.0mm	360.0mm	5m